



**TABLE I - STANDARD SPECIFICATIONS**

Unit: mm

WORKING VOLTAGE	DISC		LEAD		
	DIAMETER	THICKNESS	CODE 6: SPACING	LENGTH (for Figures A, H, I)	DIAMETER (dØ)
12V - 50V 100V	1 - 5	3.0	2.5	25.4	0.48
	5.1 - 15	3.0	5.0	25.4	0.48
	15.1	3.0	9.5	25.4	0.65
500V	1 - 7	4.0	5.0	25.4	0.65
	7.1 - 10	4.0	6.35	25.4	0.65
	10.1 - 25	4.0	9.5	25.4	0.65
1KV	1 - 10	4.0	6.35	25.4	0.65
	10.1 - 25	4.0	9.5	25.4	0.65

\* Other spacing and lead diameter available upon request

**EXAMPLES:**

**Ceramic Disc Capacitor** 1000pF / 1000 Volts / 10% / Z5U / Lead Spacing 5.0 mm / Tape & Reel Kinked Style /

CODES	(1)	(2)	(3)	(4)	(5)	(6)
PART #	<b>G</b>	<b>E</b>	<b>102</b>	<b>K</b>	<b>5</b>	<b>KR</b>

**Ceramic Disc Capacitor** 68pF / 100 Volts / 5% / NPO / Bulk / Lead Spacing 5.0mm / Lead Style Figure F / Lead Length = 42 mm

**NOTE: Non-Standard Lead Length Required**

CODES	(1)	(2)	(3)	(4)	(5)	(6)	(7)
PART #	<b>E</b>	<b>N</b>	<b>680</b>	<b>J</b>	<b>5</b>	<b>F</b>	<b>42</b>

**Ceramic Disc Capacitor** 0.01µF / 500 Volts / 20% / Z5U / Bulk / Lead Spacing 6.0mm / Lead Style Figure A

CODES	(1)	(2)	(3)	(4)	(5)	(6)
PART #	<b>F</b>	<b>E</b>	<b>103</b>	<b>M</b>	<b>6</b>	<b>A</b>

**Ceramic Disc Capacitor** 3300pF / 100 Volts / 10% / Y5P / Lead Spacing 5.0 mm / Tape & Ammo Kinked Style

CODES	(1)	(2)	(3)	(4)	(5)	(6)
PART #	<b>E</b>	<b>L</b>	<b>332</b>	<b>K</b>	<b>5</b>	<b>KA</b>

"TYPE" ON THE NEXT PAGES INCLUDE THE FOLLOWING INFORMATION TO HELP YOU BUILD A PART NUMBER

\* EXAMPLE: TYPE DN-120J (from Page 43)

CODE	(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)
PART #	<b>D</b>	<b>N</b>	<b>120</b>	<b>J</b>	<input type="text"/>	<input type="text"/>	<input type="text"/>	

AS PER CUSTOMER'S REQUIREMENT