





**RADIAL-LEADED, EPOXY-DIPPED MULTILAYER CERAMIC CAPACITORS**

RoHs Compliant

**CAPACITANCE RANGE: NPO / COG**

DIELECTRIC CODE		RD40											RD50						
SIZE CODE		50	100	250	500	1000	2000	50	100	250	500	1000	2000	50	100	250	500	1000	2000
<b>CAP</b>	0.47	R47																	
<b>(pF)</b>	0.56	R56																	
	0.68	R68																	
	0.82	R82																	
	1.0	1R0																	
	1.2	1R2																	
	1.5	1R5																	
	1.8	1R8																	
	2.2	2R2																	
	2.7	2R2																	
	3.3	3R3																	
	3.9	3R9																	
	4.7	4R7																	
	5.6	5R6																	
	6.8	6R8																	
	8.2	8R2																	
	10	100																	
	12	120																	
	15	150																	
	18	180																	
	22	220																	
	27	270																	
	33	330																	
	39	390																	
	47	470																	
	56	560																	
	68	680																	
	82	820																	
	100	101																	
	120	121																	
	150	151																	
	180	181																	
	220	221																	
	270	271																	
	330	331																	
	390	391																	
	470	471																	
	560	561																	
	680	681																	
	820	821																	
	1000	102																	
	1200	122																	
	1500	152																	
	1800	182																	
	2200	222																	
	2700	272																	
	3300	332																	
	3900	392																	
	4700	472																	
	5600	562																	
	6800	682																	
	8200	822																	
<b>CAP</b>	0.01	103																	
<b>(µF)</b>	0.012	123																	
	0.015	153																	
	0.018	183																	
	0.022	223																	
	0.027	273																	
	0.033	333																	
	0.039	393																	
	0.047	473																	
	0.056	563																	
	0.068	683																	
	0.082	823																	
	0.1	104																	
	0.12	124																	
	0.15	154																	
	0.18	184																	
	0.22	224																	
	0.27	274																	
	0.33	334																	
	0.39	394																	
	0.47	474																	